

## Tinytag Input Leads

CAB-3239, CAB-3246 & CAB-3233



### CAB-3239 Tinytag Voltage/Current Input Lead

For use with: TE-4703, TE-4704, TE-4743, TE-4744  
 TGPR-0704, TV-4704, TV-4804  
 TGRF-4703, TGRF-4704, TGRF-4743, TGRF-4744  
 TR-3703, TR-3704

Cable Length: 1.5m  
 Weight: 60g  
 Material: PVC  
 Temp Rating: -10 to +85°C  
 IP Rating: IP68 (Connector)

#### CONNECTION INFORMATION

| Colour | Pin | Function       |
|--------|-----|----------------|
| Red    | A   | DO NOT CONNECT |
| Green  | B   | N/C            |
| White  | C   | Sense Line     |
| Black  | D   | Common/0V      |
| Yellow | E   | Signal Input   |



### CAB-3246 Tinytag Current, Millivolt, Count Input Lead

For use with: TE-4804, TE-4844, TE-4901, TE-4904  
 TGPR-0804, TGPR-1001, TGPR-1201  
 TGRF-4804, TGRF-4844, TGRF-4901,  
 TGRF-4904  
 TR-1201, TR-3804

Cable Length: 1.5m  
 Weight: 35g  
 Material: PVC  
 Temp Rating: -10 to +85°C  
 IP Rating: IP68 (Connector)

#### CONNECTION INFORMATION

| Colour | Pin | Function     |
|--------|-----|--------------|
| Blue   | A   | Common/0V    |
| Red    | B   | Signal Input |



### CAB-3233 Talk Voltage/Current Input Lead

For use with: TK-4702, TK-4703, TK-4802

Cable Length: 1.5m  
 Weight: 27g  
 Material: PVC  
 Temp Rating: -10 to +85°C  
 IP Rating: IP30 (Not Waterproof)

#### CONNECTION INFORMATION

| Colour | Jack Plug | Function     |
|--------|-----------|--------------|
| White  | Tip       | Sense Line   |
| Yellow | Ring      | Signal Input |
| Black  | Shank     | Common/0V    |

### Approvals

Gemini Data Loggers (UK) Ltd. operates a Business Management System which conforms to ISO 9001 and ISO 14001.

